

Intermec

Product Profile

- Rugged, ergonomic design for full-day use
- Highly configurable and upgradeable, allowing up to 3 integrated wireless communication options in the same device
- Part of a proven and comprehensive solution set including mobile printers, centralized system and device management products, peripherals, and accessories
- Combines the power and speed of the Intel® XScale™ processor and the Microsoft® Windows Mobile for Pocket PC operating system
- Available with either integrated imaging or laser scanning technologies
- Large, transfective color display provides crisp, vivid screen for high contrast both indoors and out
- Numeric and full alphanumeric keypad options



Cisco
Compatible

7 4 1 / 7 5 1 / 7 6 1 C O L O R M O B I L E C O M P U T E R

Rugged Enterprise Mobility

Whether on the road, in the field, or on the factory floor, mobile workers demand rugged, reliable tools to do their jobs. Bringing updated technologies to the front-line worker, the Intermec® models 741, 751 and 761 mobile computers build on the proven, unprecedented success of the 700 Color Series. Designed from the ground up for use in harsh environments, the 700 device can withstand multiple 5-ft. (1.5 m) drops to concrete and is sealed against rain and dust. The ergonomic case design is sculpted and balanced, maximizing user comfort during long-term use. Radio and scanner options are integrated, not add-ons, which means they are tested to the same ruggedness standards, and don't compromise the environmental or functional characteristics of the unit.

Scaleable, Comprehensive Package

In addition to the large, brilliant color display, Intel® XScale™ processor, and Microsoft® Windows Mobile® for Pocket PC, the 700 Series' customer configurable design allows the integration of up to three radios (WLAN, WWAN, Bluetooth) in a single device. On-board wired Ethernet is standard on the 700 Series, and unlike many competitive devices, true Ethernet speeds are maintained. In addition, the built-in Flash ROM folder allows permanent storage of applications,

drivers and start-up files on non-volatile flash memory.

Data Collection

Offering both laser and imaging scanning options, Intermec's imaging technologies further enable device capabilities by enabling: omni-directional decoding - eliminating the need to line up the scan beam perpendicular to the bars; image capture - allowing for the storage of black and white photographs and signatures for applications such as proof of delivery, market surveys and field inspections; as well as decoding standard linear 1D, 2D matrix, stacked and composite barcodes.

Cross Functional Deployments

Whether your application is stand-alone, client-server, browser-based, or terminal emulation, the 700 Color is the right tool for the job. It's comprehensive feature set allows for a single device to provide cross functional capabilities. Your day's start-up activities can begin on-premise, utilizing wireless LAN access points for cross docking or load planning applications and move off-premise to the delivery vehicle, utilizing wireless wide-area voice and data services, all the while using Bluetooth compatible networking to print. **Whatever your communication requirements, the 700 Color has you covered.**

Intermec

ACCESSORIES

Complete Systems That Work

The 700 Color is part of a suite of fully-integrated system components, including a wide selection of peripherals and accessories. Intermec systems are designed to meet the needs of the business/enterprise. Applications and communication software products are available to address business process automation needs – including software to remotely configure and manage devices from a central location. The Intermec 700 Color can help businesses worldwide improve their operations, increase mobile worker efficiency, and build a better bottom line.

Portable Receipt Printers



- Rugged design built for field environment
- 2" and 4" paper options
- Lightweight, belt-clip mounting for hands-free mobility
- Bluetooth compatible wireless printing, IrDA and RS-232 serial communications
- Rechargeable customer replaceable, Lithium-Ion battery provides ample power for all-day printing
- Wireless IrDA interface to mobile computer

Physical Characteristics for models 6808, PB40 and PB41:

Dimensions:

167mm L x 172mm W x 66mm D
6.56in L x 6.8in W x 2.6in D

Weight: 932 gms (32.9 oz) with batteries and paper)

Physical Characteristics for models PB20 and 681T:

Dimensions:

144mm L x 112mm W x 616mm D
5.65in L x 4.39in W x 2.40in D

Weight: 393g (13.85 oz) without paper; 418g (14.72 oz) with paper

Workboards



- One-piece design holds 700 series securely while providing 2" or 4" printer receipts
- Lightweight, rugged and weather resistant
- Self powered with Lithium-Ion battery to support all day printing need
- Supports user downloadable character sets
- 4 Mbits of flash memory
- Power saving sleep mode
- Optional magnetic stripe/smart card reader available

Physical Characteristics for model 782T:

Dimensions:

290mm L x 213mm W x 67mm H
11.42in L x 8.40in W x 2.63in H

Weight: 815.4g (28.76oz) without paper; the weight with paper is 29.63 oz. 840 gms or 30.48 oz

Physical Characteristics for model PW40:

Dimensions:

21 cm L x 35.25 cm W x 6.7 cm H
8.24 in L x 13.9 in W x 2.62 in H

Weight: 1.13 kg (2.51 lbs.) without paper; 1.39kg (3.07 lbs.) with paper

Vehicle Dock and Cradle (shown with stand)



- Provides a secure place to store the 700 Series mobile computer in a vehicle or fork truck
- Full access to touch screen and all keys while in dock
- One-handed insertion and removal
- Two RS-232 ports for connectivity via DB-9 connector to printers and other serial devices, including long range scanners
- Option for DC power jack to support charging of the mobile computer

Physical Characteristics:

Dimensions:

159mm L x 111mm W x 58mm D
6.25in L x 6.25in W x 2.3in D

Weight: 284g (10oz)

Vehicle Dock and Cradle



- Ideal for home and small depot environments
- Charges the 700 Series mobile computer
- Supports RS-232 serial port with DB-9 connector, Active Sync cable and printers; Ethernet 10Base-T LAN; or USB host.

Physical Characteristics:

Dimensions:

114mm L x 133mm W x 64 mm
4.5in L x 5.25in W x 2.5in D

Weight: 1181g (2.6lb)

Multi-unit Depot Dock



- Holds four Intermec 700 Series mobile computers for charging and communications
- Full access to touch screens and all keys while in dock
- Ethernet 10/100 Base-T LAN connectivity with integrated switch or charge only option
- Can be mounted on a countertop or wall

Physical Characteristics:

Dimensions:

114mm L x 531mm W x 61mm D
4.5in L x 20.9in W x 2.4in D

Weight: 1658g (3.65lb)

Scan Handle



- Attaches to 700 Series without extra tools; designed for easy insertion and removal
- Handle option to allow for docking with handle attached.
- Ergonomically designed handle and trigger mechanism allows for fatigue-free use
- 700 is positioned horizontally for convenient access to display and keypad
- Access to the 700 Series battery compartment allows the user to change the battery pack without removing the handle

Physical Characteristics (with 700 installed):

Size: 3.7" x 7.5" x 1.7" (94x191x43mm) plus 2.0" x 4.6" x 1.1" (51x117x28mm) volume at base of the handle for the handle grip (handle and handheld overall dimensions)

Weight: 624g (22oz)

Adapter Modules

The 700 Series adaptation of snap-on modules accessories easily enables applications requiring support for long-range scanning; mag stripe reading (MSR) and dial-up modem capabilities.

Mag Stripe Reader



- Reads cards up to .055 inches (1.4 mm) thick
- Supports ANSI, ISO, AAMVA, CA DMV and User Configurable Generic Formats
- Snap on retainment features for temporary attachment
- Thumb screws for semi-permanent attachment
- Ability to charge unit via cable or dock while adapter is attached.
- Battery accessible with module attached

Dimensions:

3.55in W x 3.25in L x 1.45in D

3.3 v to 5 Volt Scanner Adapter



- 3.3 V to 5 V Boost converter with DB9M RS-232 interface
- Supports 1550, 1551 and 1400 Intermec scanners
- Snap on retainment features for temporary attachment
- Attachable with thumb screws for semi-permanent attachment
- Battery accessible with module attached

Dimensions:

3.52 in W x 2.63in L x 1.39in D

Snap-On Modem



- Supports V.90 for download speeds upto 56 Kbps
- LED's to indicate connection status
- Connects to a standard RJ-11 phone jack
- Battery accessible with module attached
- Ability to charge unit via cable while adapter is attached.

Dimensions:

3.55in W x 3.45in L x 1.45in D

Accessories



The Intermec 700 series support a full line of accessory items including: holsters, carry cases, multi-pack external battery charger, power and data cables, compact flash and secure digital cards.

Physical Characteristics**Length:** 191 mm (7.53 in.)**Width:** 90 mm (3.5 in.)**Height:** 50 mm (1.97 in.)**Weight:** 483-568 grams (17-20 oz) depending on options**Environmental****Operating Temp:**

-20° to +60°C (-4° to +140°F)

Storage Temp:

-20° to +60°C (-4° to +140°F)

Relative Humidity:

5% to 95% (non-condensing)

Rain and Dust Resistance:

IP64 compliant

Drop Spec: 5' drop, 26 times onto concrete**Power****Battery Type:** Lithium-Ion, 7.2V, (2 x 2000 mAh cells), customer replaceable**Battery Capacity:** 14.4 Watt-hours**Battery Life:** 8-12 hours, application dependent**Recharging Time:** 4 hours**Operating System**

Microsoft® Windows® for Pocket PC

Microprocessor

Intel® XScale™ Processor, 400 MHz

Memory and Storage**RAM Memory:** 64 MB (128 MB optional)**Flash ROM:** 64 MB; includes ROM folder for application storage**Internal Slots**

- Secure Digital (SD)
- CompactFlash (CF) Type II

Display

Transflective, 240x320 pixels, 3.8 in. (97 mm) diagonal, 256 K colors

Standard Communications

RS232

IrDA 1.1 (115 kbps)

10 Base-T Ethernet

USB Client

Integrated Radio Options**LAN:** 802.11b/g (Wi-Fi certified)**WAN:** GSM/GPRS, CDMA/1XRTT

Bluetooth™ compatible module

Modem

- Optional V.90 modem snaps on to 700 Color
- V.92 docking options

Integrated Scanner Options

- Area imager
- Linear imager
- 1D laser
- PDF 417 laser

Keypad Options

- Numeric
- Full alphanumeric

Cisco Compatible

Version 1

Version 2 (future)

Regulatory Approvals

FCC Part 15 Class B

UL Listing


CE Mark

CB Report

* Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

Microsoft, Windows, the Windows logo, Windows Media, Outlook, and ActiveSync are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Intel® and XScale™ are trademarks of Intel Corporation.



Intermec®
e x p e c t **MORE®**

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

**Europe/
Middle East & Africa
Headquarters**

Sovereign House
Vastern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86.10.5165.5922
Fax: 86.10.6567.6778

Australia

Level 7, 200 Pacific Highway
Crows Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

**South America & Mexico
Intermec South America Ltda.**

Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611587-01C 07/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.